

Pro connexion

 **Alumetal**
Import

Product type: **Pro connexion kabelhaspel**

Ref. N°: **250400** **Kabelhaspel H07RN-F 3G2,5 – 25m**
 400400 **Kabelhaspel XL H07RN-F 3G2,5 – 40m**

Certificaat houder:

Alumetal bvba
Vlasbloemstraat 10
8750 Zwevezele
België

Alumetal bvba verklaart dat bovengenoemde producten voldoen aan de veiligheidseisen van de Europese richtlijnen.

Opgemaakt op 05/10/2015

CERTIFICAAT



Test Verification of Conformity


On the basis of the referenced test report(s), the sample(s) of the below product has been found to comply with the relevant harmonized standard(s) to the directive(s) listed on this verification at the time the tests were carried out.

The manufacturer may indicate compliance to only the said directives by signing a DoC himself and may affix the CE marking to products identical to the tested sample(s) if the product complies with all CE marking directives that has the product in their scope. In addition, the manufacturer shall file and keep the documentation according to the rules of the applicable directive(s) and shall consider changes of the standards as they may occur. Additional requirements, additional directives and local laws may be applicable.

Applicant Name & Address : [REDACTED]
Manufacturer Name & Address : [REDACTED]
Product(s) Tested : Cable reel
Ratings and principal characteristics : Non-rewirable, 230Vac, IP44, Class I, with a thermal cut-out, with 4 way panel type NF C 61-314 socket outlet with shutters, with self closing waterproof lid, with a non-rewirable plug with cord H05RR-F 3G1,5-2,5mm² or H07RN-F 3G1,5-2,5mm², detail product information see attachment.
Model(s) : [REDACTED]
Brand name : [REDACTED]
Relevant Standard(s) / Specification(s) / Directive(s) : The Low Voltage Directive 2006/95/EC
Verification Issuing Office Name & Address : Intertek Testing Services Shanghai
Building No.86, 1198 Qinzhou Road (North), Shanghai 200233, China
Verification Number : SH10060800-V1
Report Number(s) : SH10060800-001
SH10060800-002

NOTE 1: This verification is part of the full test report(s) and should be read in conjunction with it.

This Verification is for the exclusive use of Intertek's Client and is provided pursuant to the agreement between Intertek and its Client. Intertek's responsibility and liability are limited to the terms and conditions of the agreement. Intertek assumes no liability to any party, other than to the Client in accordance with the agreement, for any loss, expense or damage occasioned by the use of this Verification. Only the Client is authorized to copy or distribute this Verification. Any use of the Intertek name or one of its marks for the sale or advertisement of the tested material, product or service must first be approved in writing by Intertek. The observations and test results referenced from this Verification are relevant only to the sample tested. This Verification by itself does not imply that the material, product, or service is or has ever been under an Intertek certification program.



Leo Shi
Manager
June 25, 2010


Annex to Test Verification of Conformity

This is an Annex to Test Verification of Conformity with SH10060800-V1. The issuing office is Intertek Testing Services Shanghai Building No.86, 1198 Qinzhou Road (North), Shanghai 200233, China

Type	Max Rated Power full-reeled / unreeled	Cord Information	Outer Dia. (mm)	Remark
XP01-F	1000W(4,34A)/ 3000W(13,04A)	H05RR-F 3G1,5 mm ² , Max.length 50m,	Φ280	Plastic enclosure, with shutter, with metal frame
	1200W(5,21A)/ 3600W(15,65A)	H05RR-F 3G2,5mm ² , Max.length 50m,	Φ280	
	1000W(4,34A)/ 3000W(13,04A)	H07RN-F 3G1,5 mm ² , Max.length 50m,	Φ280	
	1200W(5,21A)/ 3600W(15,65A)	H07RN-F 3G2,5mm ² , Max.length 40m,	Φ280	
XP03-F	1000W(4,34A)/ 3000W(13,04A)	H05RR-F 3G1,5 mm ² , Max.length 25m,	Φ235	Plastic enclosure, with shutter, with metal frame
	1000W(4,34A)/ 3000W(13,04A)	H07RN-F 3G1,5 mm ² , * Max.length 25m,	Φ235	
XP06-F	1000W(4,34A)/ 3000W(13,04A)	H05RR-F 3G1,5 mm ² , Max.length 50m,	Φ280	Plastic enclosure, with shutter, with metal frame
	1200W(5,21A)/ 3600W(15,65A)	H05RR-F 3G2,5mm ² , Max.length 50m,	Φ280	
	1000W(4,34A)/ 3000W(13,04A)	H07RN-F 3G1,5 mm ² , Max.length 50m,	Φ280	
	1200W(5,21A)/ 3600W(15,65A)	H07RN-F 3G2,5mm ² , Max.length 40m,	Φ280	

NOTE: This annex is part of the Test Verification of Conformity and should be read in conjunction with it.

This Verification is for the exclusive use of Intertek's Client and is provided pursuant to the agreement between Intertek and its Client. Intertek's responsibility and liability are limited to the terms and conditions of the agreement. Intertek assumes no liability to any party, other than to the Client in accordance with the agreement, for any loss, expense or damage occasioned by the use of this Verification. Only the Client is authorized to copy or distribute this Verification. Any use of the Intertek name or one of its marks for the sale or advertisement of the tested material, product or service must first be approved in writing by Intertek. The observations and test results referenced from this Verification are relevant only to the sample tested. This Verification by itself does not imply that the material, product, or service is or has ever been under an Intertek certification program.



Leo Shi
Manager
June 25, 2010